moooi

Non Random

BERTJAN POT



Old ladies call them neatly coiled balls of yarn, Kids talk about soap bubbles hanging from lightbulbs. Some say they are there to light up Arabian nights, Moooi says they're Non Random Lights.

Detailing



Non Random does not shine a random light: the production of its shape is, unlike the Random Light, completely mechanically pre-programmed.

Colours

Black

White

Non Random / Non Random D48

Dimensions

48cm | 18.9"



34cm | 21.3

Product

Packaging

 $\begin{array}{lll} \mbox{width } 48\mbox{cm} \, | \, 18.9 \mbox{"} & \mbox{width } 55\mbox{cm} \, | \, 21.7 \mbox{"} \\ \mbox{height } 54\mbox{cm} \, | \, 21.3 \mbox{"} & \mbox{height } 63\mbox{cm} \, | \, 24.8 \mbox{"} \\ \mbox{depth } 48\mbox{cm} \, | \, 18.9 \mbox{"} & \mbox{cubage } 0.19\mbox{m}^3 \, | \, 6.73\mbox{ft}^3 \mbox{} \\ \mbox{diameter } 48\mbox{cm} \, | \, 18.9 \mbox{"} & \mbox{length } 55\mbox{cm} \, | \, 21.7 \mbox{"} \\ \mbox{weight } 8.16\mbox{lbs} \mbox{"} \\ \mbox{weight } 3.7\mbox{kg} \, | \, 8.16\mbox{lbs} \end{array}$

Technical CE

MATERIAL

Sphere from fiberglass with epoxy resin, powder coated aluminium cap, anodized aluminium reflector

ENERGY LABEL INSTALLATION REQUIRED

A++ to E Yes

LIGHTSOURCE TYPE NUMBER OF LIGHTSOURCES

Incandescent

SHAPE INPUT VOLTAGE
Globe 220-240

FREQUENCY MAX POWER CONSUMPTION

50/60 60W

DIMMABLE LAMPHOLDER

Yes E27

CABLE COLOURCABLE LENGTHBlack400cm | 157.5"

CANOPYPebble II Black, ABS
All directions

Technical cULus

MATERIAL

Sphere from fiberglass with epoxy resin, powder coated aluminium cap, anodized aluminium reflector

ENERGY LABEL INSTALLATION REQUIRED

A++ to E

LIGHTSOURCE TYPE

Incandescent

SHAPE Globe

FREQUENCY 50/60

DIMMABLE Yes

CABLE COLOUR Black

CANOPYChrome Canopy

NUMBER OF LIGHTSOURCES

1

INPUT VOLTAGE 110-130

MAX POWER CONSUMPTION

60W

LAMPHOLDER

E26

CABLE LENGTH 400cm | 157.5"

All directions

Non Random / Non Random D71

Dimensions

71cm | 28"



) ocm | 2/.6

Product

width $7 \text{lcm} \mid 28"$ Height $70 \text{cm} \mid 27.6"$ DEPTH $7 \text{lcm} \mid 28"$ DIAMETER $7 \text{lcm} \mid 28"$ WEIGHT NETTO $1.5 \text{kg} \mid 3.31 \text{lbs}$ Packaging

WIDTH 75cm | 29.5"
HEIGHT 82cm | 32.3"
CUBAGE 0.46m³ | 16.29ft³
LENGTH 75cm | 29.5"
WEIGHT 6kg | 13.23lbs

Technical CE

MATERIAL

Sphere from fiberglass with epoxy resin, powder coated aluminium cap, anodized aluminium reflector

ENERGY LABEL

A++ to E

LIGHTSOURCE TYPEIncandescent

SHAPE Globe

FREQUENCY 50/60

INSTALLATION REQUIRED

Yes

NUMBER OF LIGHTSOURCES

1

INPUT VOLTAGE 220-240

MAX POWER CONSUMPTION

60W

DIMMABLE LAMPHOLDER

Yes E27

CABLE COLOURCABLE LENGTHBlack400cm | 157.5"

CANOPYPebble II Black, ABS
All directions

Technical cULus

MATERIAL

Sphere from fiberglass with epoxy resin, powder coated aluminium cap, anodized aluminium reflector

ENERGY LABEL INSTALLATION REQUIRED

A++ to E

LIGHTSOURCE TYPE NUMBER OF LIGHTSOURCES

Incandescent

SHAPE INPUT VOLTAGE
Globe 110-130

FREQUENCY MAX POWER CONSUMPTION

50/60 60W

DIMMABLE LAMPHOLDER

Yes E26

CABLE COLOURCABLE LENGTHBlack400cm | 157.5"

CANOPY LIGHT DIRECTION
Chrome Canopy All directions

Dimmer

For fluent dimming behaviour we advise a dimmer that is compatible with the following specs.

DIMMER TYPE

Mains dimi

Mains dimmable with compatible light source

Please note the functioning of the dimmer and the power supply combination can never be predicted, it always needs to be tested in practice.