



DESCRIPTION

The suspended structure's rigorous profiles are delineated by light that, filtering through the micro-holes, creates a quiet atmosphere. Urban Lighline Suspension's light burnished brass core is located within a micro-perforated matte black or gold metal lampshade, which shields the light. Urban Lightline is also available in a wall version.

PRODUCTS DETAILS	FUNCTION	SUSPENSION
	LOCATION	INTERIOR
	LIGHT EMISSION	DIRECT AND INDIRECT LIGHT
	LIGHT SOURCE	STRIP LED 16,8W/m 2700°K 1900lm/m CRI 90 24Vdc
		TOT. = 49W 5510lm
	ENERGY EFFICIENCY	C
	RATED VOLTAGE	110 - 120V / 220 - 240V
	FREQUENCY	50 - 60Hz
	SUPPLY	TERMINAL BLOCK
	BALLAST	BALLAST INCLUDED
	WIRING CABLE LENGTH	250 cm (98"4)
	STEEL CABLE LENGTH	250 cm (98"4)
DALI or TRIAC dimming kit available upon request		

CERTIFICATION

UL
WIRED

CE

IP20

MATERIALS

STRUCTURE

M11+ MB LIGHT BURNISHED BRASS + MATTE BLACK

PACKAGE	QTY	DIMENSIONS	NET WEIGHT	GROSS WEIGHT	TOTAL VOL.
	1 × BOX	180 × 36 × H 27 cm (70"9 × 14"2 × H 10"6)	6 kg	8 kg	0,17 m³

