



DESCRIPTION

The Beak Ceiling/Wall's adjustable cylinder directs and projects a beam of direct light. Its smooth, burnished brass finish is accented by knurling on the head, adding visual rhythm to the structure. Also available in a Flat version with a reduced-thickness canopy, Beak Ceiling/Wall can be installed on both walls and ceilings, making it ideal for contract settings. Beak is also available in floor, table, suspension, picture, reading versions and another ceiling model.

PRODUCTS DETAILS	FUNCTION	CEILING/WALL
	LOCATION	INTERIOR
	LIGHT EMISSION	DIRECTIONAL LIGHT
	LIGHT SOURCE	COB LED CLU703 6W 724lm 700mA 9V CRI90 2700°K
	ENERGY EFFICIENCY	F
	RATED VOLTAGE	110 - 120 V / 220 - 240 V
	FREQUENCY	50 - 60Hz
	SUPPLY	BEAK CEILING/WALL TERMINAL BLOCK
		BEAK CEILING/WALL FLAT REMOTE TERMINAL BLOCK
	LENS SPOT BEAM	18° - 36° - 60°
BEAK CEILING/WALL: DALI or TRIAC dimming kit available upon request		
BEAK CEILING/WALL FLAT: DALI or TRIAC remote dimming kit available upon request		
On/off Switch and Dimmable Switch to be combined upon request		

CERTIFICATION

UL/C_E    IP20

MATERIALS	STRUCTURE	
	M11	LIGHT BURNISHED BRASS
	M12	DARK BURNISHED BRASS

PACKAGE	QTY	DIMENSIONS	NET WEIGHT	GROSS WEIGHT	TOTAL VOL.
	1 × BOX	15 × 15 × H 30 cm (5"9 × 5"9 × 11"8)	0,8 kg	1,1 kg	0,006 m ³

DIMENSIONS

BEAK CEILING/WALL STANDARD

Ø 9 cm (3"5)

21 cm (8"3)

90°

360°

NORTH AMERICAN WALL PLATE

Ø 14 cm (5"5)

21 cm (8"3)

90°

360°

BEAK CEILING/WALL FLAT STANDARD

Ø 8 cm (3"1)

18 cm (7")

90°

360°

NORTH AMERICAN WALL PLATE

Ø 11 cm (4"3)

18 cm (7")

90°

360°