



DESCRIPTION

Beak Reading is designed for precise illumination in intimate and reading settings, directing a focused beam through an adjustable head with reduced diameter. The burnished brass defines the element, while the contrast between the smooth surface and the knurled detail of the head introduces depth and a measured material rhythm. Beak Reading is also available in Flat version and with an integrated on/off button. Beak collection includes ceiling, wall, picture, table, floor, and suspension models.

PRODUCTS DETAILS	FUNCTION	WALL - READING LIGHT
	LOCATION	INTERIOR
	LIGHT EMISSION	DIRECTIONAL LIGHT
	LIGHT SOURCE	DOT METAL SPOT 1W 119lm 350mA 2,9V CRI+80 2700°K
	ENERGY EFFICIENCY	D
	RATED VOLTAGE	110 - 120 V / 220 - 240 V
	FREQUENCY	50 - 60Hz
	SUPPLY	BEAK READING TERMINAL BLOCK BEAK READING FLAT REMOTE TERMINAL BLOCK
	LENS SPOT BEAM	60°
	BEAK READING: DALI or TRIAC dimming kit available upon request	
	BEAK READING FLAT: DALI or TRIAC remote dimming kit available upon request	
	On/off Switch and Dimmable Switch to be combined upon request.	

CERTIFICATION

UL / CE   IP20

MATERIALS	STRUCTURE	
	M11	LIGHT BURNISHED BRASS
	M12	DARK BURNISHED BRASS

PACKAGE	QTY	DIMENSIONS	NET WEIGHT	GROSS WEIGHT	TOTAL VOL.
	1 × BOX	13,5 × 13,5 × H 27 cm (5"3 × 5"3 × 10"6)	0,5 kg	1 kg	0,005 m³


DIMENSIONS

BEAK READING STANDARD

Ø 9 cm (3"5)

7 cm (2"7)

14 cm (5"5)




NORTH AMERICAN WALL PLATE

Ø 14 cm (5"5)

7 cm (2"7)

16 cm (6"3)




BEAK READING FLAT STANDARD

Ø 8 cm (3"2)

5 cm (2")

13,5 cm (5"3)




NORTH AMERICAN WALL PLATE

Ø 11 cm (4"3)

5 cm (2")

15 cm (5"9)



VENICEM

V.02 2026 | 2/3
FOR MORE INFORMATION VISIT [VENICEM.COM](https://www.venicem.com)

DESCRIPTION

Beak Reading is designed for precise illumination in intimate and reading settings, directing a focused beam through an adjustable head with reduced diameter. The burnished brass defines the element, while the contrast between the smooth surface and the knurled detail of the head introduces depth and a measured material rhythm. Beak Reading is also available in Flat version and with an integrated on/off button. Beak collection includes ceiling, wall, picture, table, floor, and suspension models.

PRODUCTS DETAILS	FUNCTION	WALL - READING LIGHT
	LOCATION	INTERIOR
	LIGHT EMISSION	DIRECTIONAL LIGHT
	LIGHT SOURCE	DOT METAL SPOT 1W 119lm 350mA 2,9V CRI+80 2700°K
	ENERGY EFFICIENCY	D
	RATED VOLTAGE	110 - 120 V / 220 - 240 V
	FREQUENCY	50 - 60Hz
	SUPPLY	BEAK READING - ON/OFF SWITCH TERMINAL BLOCK BEAK READING FLAT - ON/OFF SWITCH REMOTE TERMINAL BLOCK
	LENS SPOT BEAM	60°

CERTIFICATION

UL

WIRE

/

C

E

IP20

MATERIALS	STRUCTURE	
	M11	LIGHT BURNISHED BRASS
	M12	DARK BURNISHED BRASS

PACKAGE	QTY	DIMENSIONS	NET WEIGHT	GROSS WEIGHT	TOTAL VOL.
	1 × BOX	13,5 × 13,5 × H 27 cm (5"3 × 5"3 × 10"6)	0,5 kg	1 kg	0,005 m³

DIMENSIONS

BEAK READING - ON/OFF SWITCH
STANDARD

Ø 9 cm (3"5)

7 cm (2"7)

13 cm (5"1)

360°

90°

NORTH AMERICAN WALL PLATE

Ø 14 cm (5"5)

7 cm (2"7)

15 cm (5"9)

360°

90°

BEAK READING FLAT - ON/OFF SWITCH
STANDARD

Ø 8 cm (3"2)

5 cm (2")

12,5 cm (4"9)

360°

90°

NORTH AMERICAN WALL PLATE

Ø 11 cm (4"3)

5 cm (2")

14 cm (5"5)

360°

90°

VENICEM

V.02 2026 | 3/3
FOR MORE INFORMATION VISIT [VENICEM.COM](https://www.venicem.com)